



US009080736B1

(12) **United States Patent**  
**Salzinger et al.**

(10) **Patent No.:** **US 9,080,736 B1**  
(45) **Date of Patent:** **Jul. 14, 2015**

(54) **PORTABLE SOLAR-POWERED DEVICES**

H05B 37/4218; H05B 37/0236; H05B 37/0227; F21Y 2101/02

(71) Applicant: **MPOWERD Inc.**, New York, NY (US)

See application file for complete search history.

(72) Inventors: **John Salzinger**, Brooklyn, NY (US);  
**Michael Muchleemann**, Elbridge, NY (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **MPOWERD INC.**, New York, NY (US)

5,888,156 A 3/1999 Cmiel  
5,947,581 A 9/1999 Schrimmer et al.  
6,193,392 B1 2/2001 Lodhie  
7,377,667 B2 5/2008 Richmond  
7,690,812 B2 4/2010 Roberts  
7,857,490 B1 12/2010 Fett

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

(21) Appl. No.: **14/619,307**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Feb. 11, 2015**

CA 152065 5/2014  
CN 1162496 A 10/1997

(Continued)

**Related U.S. Application Data**

(60) Provisional application No. 62/106,553, filed on Jan. 22, 2015.

OTHER PUBLICATIONS

(51) **Int. Cl.**

**F21L 4/08** (2006.01)  
**F21V 15/01** (2006.01)  
**H05B 33/08** (2006.01)  
**H05B 37/02** (2006.01)  
**F21V 23/04** (2006.01)  
**F21Y 101/02** (2006.01)

Goering, L., "Blow-up Solar Lantern Lights up Haiti's Prospects," Thomson Reuters Foundation, Jun. 22, 2012 (4 pages), available at <http://www.trust.org/item/20120622150100-k9yos>.

(Continued)

(52) **U.S. Cl.**

CPC ..... **F21L 4/08** (2013.01); **F21V 15/012** (2013.01); **F21V 23/0414** (2013.01); **H05B 33/0809** (2013.01); **H05B 33/0845** (2013.01); **H05B 33/0857** (2013.01); **H05B 33/0872** (2013.01); **H05B 37/0218** (2013.01); **H05B 37/0227** (2013.01); **H05B 37/0236** (2013.01); **H05B 37/0272** (2013.01); **F21Y 2101/02** (2013.01)

*Primary Examiner* — John A Ward

(74) *Attorney, Agent, or Firm* — Bookoff McAndrews, PLLC


(58) **Field of Classification Search**

CPC ..... F21L 4/08; F21V 15/012; F21V 37/0414; H05B 33/0809; H05B 33/0857; H05B 33/0872; H05B 33/0845; H05B 37/0872;

(57) **ABSTRACT**

Solar-powered lighting devices that may be portable and/or collapsible are described. The devices may include a housing including a first wall, a second wall, and one or more side walls between the first wall and the second wall, at least one solar panel to generate solar energy, and a rechargeable battery to store the solar energy generated. The devices may include a plurality of operating modes for controlling lights within the housing, and a microprocessor for controlling the operating modes.

**20 Claims, 15 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

8,845,126	B1 *	9/2014	Martzall .....	362/183
2005/0265029	A1	12/2005	Epstein et al.	
2007/0014125	A1	1/2007	Chu	
2008/0013317	A1 *	1/2008	Hinds .....	362/286
2008/0175006	A1	7/2008	Kellmann et al.	
2011/0018439	A1	1/2011	Fabbri	
2012/0120642	A1 *	5/2012	Sreshta et al. ....	362/183
2012/0193660	A1	8/2012	Donofrio	
2012/0224359	A1	9/2012	Chun	
2014/0118997	A1	5/2014	Snyder	
2014/0146525	A1	5/2014	Lueptow	

FOREIGN PATENT DOCUMENTS


CN	101576204	A	11/2009
CN	101690402	A	3/2010

CN	101886746	A	11/2010
CN	201715273	U	1/2011
CN	102116415	A	7/2011
CN	102403929	A	4/2012
CN	202203682	U	4/2012
CN	202511013	U	10/2012
CN	202884514	U	4/2013
CN	203215307	U	9/2013
CN	203489018	U	3/2014
CN	302782955	S	3/2014
EP	002289363-0001		8/2013


OTHER PUBLICATIONS

Patent Evaluation Report for Chinese Application No. ZL201320570977.8, dated Feb. 26, 2014 (87 pages).  
 Jonsson, J. Project Soul Cell, YouTube, Oct. 28, 2009 (1 page), available at <http://www.youtube.com/watch?v=DG7IkgUUr4M>.


\* cited by examiner




**FIG. 1A**




**FIG. 1B**




**FIG. 1C**




**FIG. 1D**




**FIG. 2A**




**FIG. 2B**



**FIG. 3A**




**FIG. 3B**




**FIG. 3C**







**FIG. 4A**




**FIG. 4B**




**FIG. 4C**




**FIG. 5**




**FIG. 6A**




**FIG. 6B**




**FIG. 7A**




**FIG. 7B**




**FIG. 8**




**FIG. 9A**




**FIG. 9B**



**FIG. 10A**




**FIG. 10B**



**FIG. 11**




1200



**FIG. 12A**

1200



**FIG. 12B**

**PORTABLE SOLAR-POWERED DEVICES****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims priority to U.S. Provisional Application No. 62/106,553 filed on Jan. 22, 2015, which is incorporated herein by reference in its entirety.

**TECHNICAL FIELD**

The present disclosure generally relates to solar-powered lighting devices. More particularly, embodiments of the present disclosure include portable, rechargeable lighting devices, such as lanterns powered by solar energy.

**BACKGROUND**

Certain situations require alternative lighting solutions, such as during limited or interrupted power access, or a lack of power altogether. Examples include cases of natural disaster and other emergencies, remote/rural locations far from a power station or electricity grid, and developing countries that have limited and/or unreliable power. Yet, current lighting options are often short-lived, unreliable, inefficient, non-reusable/non-rechargeable, impractical, and/or expensive to produce and operate.

**SUMMARY OF THE DISCLOSURE**

A collapsible solar-powered lighting device comprising a housing including a first wall, a second wall opposite the first wall, and one or more side walls extending between the first wall and the second wall, wherein the first wall, second wall, and one or more side walls define an inflatable bladder; at least one solar panel integrated into an outside surface of at least one of the first wall and the second wall, thereby defining the at least one of the first wall and the second wall that includes the at least one solar panel as an electronics wall of the housing; a plurality of light-emitting diodes (LEDs) integrated into an inside surface of the electronics wall of the housing, the plurality of LEDs forming a generally annular arrangement and facing an interior of the housing; a rechargeable battery integrated into the electronics wall between the inside surface of the electronics wall and the outside surface of the electronics wall, the rechargeable battery being electrically connected between the at least one solar panel and the plurality of LEDs, such that the rechargeable battery is configured to supply current to the plurality of LEDs and be recharged by the at least one solar panel; a button integrated into one or more of the first wall, the second wall, and the one or more side walls, the button being selectable by a user to control an operating mode of the plurality of LEDs; a microprocessor integrated into the electronics wall of the housing between the inside surface of the electronics wall and the outside surface of the electronics wall, the microprocessor being electrically connected to the button, the rechargeable battery, and the plurality of LEDs; and a current regulator coupled between the rechargeable battery and the microprocessor, the current regulator maintaining a threshold current delivered to the plurality of LEDs as controlled by the microprocessor; wherein the microprocessor is configured to control a plurality of operating modes of the LEDs, at least one of the operating modes including changing a color of light emitted from the housing such that a first press of the button causes the plurality of LEDs to emit a first color of light, a second press of the button causes the plurality of LEDs to emit a

second color of light, a third press of the button causes the plurality of LEDs to emit a third color of light, and an nth press of the button causes the plurality of LEDs to initiate a transition sequence, the transition sequence causing the plurality of LEDs to begin emitting the first color of light, gradually change to the second color of light, gradually change to the third color of light, and gradually change to the nth color of light.

The present disclosure further includes an inflatable solar-powered lighting device comprising: a housing including a first wall, a second wall opposite the first wall, and one or more side walls extending between the first wall and the second wall, wherein the first wall, second wall, and one or more side walls define an airtight inflatable bladder; at least one solar panel integrated into an outside surface of at least one of the first wall and the second wall; a plurality of light-emitting diodes (LEDs) integrated into an inside surface of the at least one of the first wall and the second wall, the plurality of LEDs arranged in a generally annular arrangement and facing an interior of the airtight inflatable bladder defined by the first wall, second wall, and one or more side walls; a rechargeable battery integrated into the at least one of the first wall and the second wall between the inside surface of the at least one of the first wall and the second wall and the outside surface of the at least one of the first wall and the second wall, the rechargeable battery being electrically connected between the at least one solar panel and the plurality of LEDs, such that the rechargeable battery is configured to supply current to the plurality of LEDs and be recharged by the at least one solar panel; a button integrated into one or more of the first wall, the second wall, and the one or more side walls, the button being selectable by a user to control an operating mode of the plurality of LEDs; a microprocessor integrated into the at least one of the first wall and the second wall between the inside surface of the at least one of the first wall and the second wall and the outside surface of the at least one of the first wall and the second wall, the microprocessor being electrically connected between the button, the battery, and the plurality of LEDs; and a current regulator coupled between the rechargeable battery and the microprocessor, the current regulator maintaining a threshold current delivered to the plurality of LEDs as controlled by the microprocessor; wherein the microprocessor is configured to control a plurality of operating modes of the LEDs, at least one of the operating modes including changing a color of light emitted from the housing.

The present disclosure further includes a collapsible solar-powered lighting device comprising: a housing including a first wall, a second wall opposite the first wall, and one or more side walls extending between the first wall and the second wall, wherein the first wall, second wall, and one or more side walls define an inflatable bladder; at least one solar panel integrated into an outside surface of at least one of the first wall and the second wall, the solar panel defining the at least one of the first wall and the second wall as an electronics wall of the housing; a plurality of light-emitting diodes (LEDs) integrated into an inside surface of the electronics wall of the housing, the plurality of LEDs arranged in a generally annular arrangement and facing an interior of the inflatable bladder defined by the first wall, second wall, and one or more side walls; a rechargeable battery integrated into the electronics wall of the housing between the inside surface of the electronics wall and the outside surface of the electronics wall, the rechargeable battery being electrically connected between the at least one solar panel and the plurality of LEDs, such that the rechargeable battery is configured to supply current to the plurality of LEDs and be recharged by the at

least one solar panel; a button integrated into one or more of the first wall, the second wall, and the one or more side walls, the button being selectable by a user to control an operating mode of the plurality of LEDs; and a microprocessor integrated into the electronics wall of the housing between the inside surface of the electronics wall and the outside surface of the electronics wall, the microprocessor being electrically connected between the button, the battery, and the plurality of LEDs; wherein the microprocessor is configured to control a plurality of operating modes of the LEDs, at least one of the operating modes including changing a color of light emitted from the housing such that a first press of the button causes the plurality of LEDs to emit a first color of light, a second press of the button causes the plurality of LEDs to emit a second color of light, and a third press of the button causes the plurality of LEDs to emit a third color of light.

### BRIEF DESCRIPTION OF THE FIGURES

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate various exemplary embodiments and together with the description, serve to explain the principles of the disclosed embodiments.

FIGS. 1A-1D show an exemplary device, in accordance with one or more embodiments of the present disclosure, wherein FIG. 1C shows an exploded view of the device of FIG. 1A, and FIG. 1D shows an exemplary design on the device of FIG. 1A.

FIGS. 2A and 2B show an exemplary device, in accordance with one or more embodiments of the present disclosure.

FIGS. 3A-3C show an exemplary device, in accordance with one or more embodiments of the present disclosure, wherein FIG. 3C shows an exploded view of the device of FIG. 3A.

FIGS. 4A-4C show an exemplary device, in accordance with one or more embodiments of the present disclosure.

FIG. 5 shows exemplary packaging for devices according to embodiments of the present disclosure.

FIGS. 6A and 6B illustrate exemplary devices, in accordance with one or more embodiments of the present disclosure.

FIGS. 7A and 7B illustrate exemplary devices, in accordance with one or more embodiments of the present disclosure.

FIG. 8 illustrates an exemplary device, in accordance with one or more embodiments of the present disclosure.

FIGS. 9A and 9B illustrate exemplary devices, in accordance with one or more embodiments of the present disclosure.

FIGS. 10A and 10B illustrate exemplary devices, in accordance with one or more embodiments of the present disclosure.

FIG. 11 illustrates an exemplary device, in accordance with one or more embodiments of the present disclosure.

FIGS. 12A and 12B show an exemplary device, in accordance with one or more embodiments of the present disclosure.

### DETAILED DESCRIPTION

Embodiments of the present disclosure include solar-powered lighting devices that may be portable and/or collapsible.

FIGS. 1A-1C illustrate an exemplary lighting device 100 comprising an inflatable housing 101, such that the device 100 may have a collapsed configuration (e.g., for storage, recharging, or otherwise when not in use) and an expanded, inflated configuration (e.g., for use). The housing 101 may

include a first wall 102, a second wall 104, and one or more side walls 106 between the first wall 102 and the second wall 104, wherein the side wall(s) 106 may be collapsible, e.g., to allow the device 100 to deflate and inflate. For example, the first wall 102, second wall 104, and one or more side walls 106 may define an inflatable bladder. The first wall 102 and the second wall 104 may be positioned opposite each other, e.g., generally parallel, or any other suitable configuration. The devices of the present disclosure are not limited to any particular orientation for storage and/or while in use. For example, any of the first wall 102, the second wall 104, or the side wall(s) 106 of device 100 may have an upward-facing orientation during use. Further, the orientation of the device 100 may be changed during use.

In some embodiments, the device 100, e.g., the housing 101 of the device 100, may be airtight and/or watertight. For example, the device 100 may be airtight and/or watertight in accordance with various industrial standards or codes.

The housing 101 may have a generally cylindrical shape, as shown in FIG. 1A (top view) and FIG. 1B (bottom view), comprising one generally cylindrical side wall 106. For example, the first and second walls 102, 104 may be planar, and may have one generally cylindrical side wall 106 therebetween. For example, the first and/or second walls 102, 104 may be circular (as shown in FIGS. 1A and 1B), oval, or polygonal in shape (e.g., square, rectangular, triangular, hexagonal, octagonal, etc.). The first and second walls 102, 104 may have the same size, or may have different sizes. For example, the first wall 102 may be larger than the second wall 104, such that the housing 101 is tapered and wider towards the first end, or the second wall 104 may be larger than the first wall 102, such that the housing 101 is tapered and wider towards the second end. In some embodiments, at least a portion of the first wall 102 and/or the second wall 104 may be foldable. For example, the first wall 102 and/or the second wall 104 may be configured to fold, e.g., to achieve a smaller cross-sectional area or volume in the collapsed configuration.

The side wall(s) 106 may correspond to the shape of the first and/or second walls 102, 104. For example, the housing 101 may include polygonal first and second walls 102, 104, and a plurality of side walls 106 corresponding in number to the number of sides of the polygon. In some embodiments, the first and/or second walls 102, 104 may be three-dimensional, e.g., providing for a housing 101 having a spherical or polyhedral shape (e.g., cube, pyramid, rectangle, star, etc.). For example, the housing 101 may have a spherical shape and include a soccer ball design or a beach ball design incorporated into the housing 101. The housing 101 may include any combination of first wall 102, second wall 104, and side wall(s) 106. For example, the first wall 102 may have a three-dimensional shape, such as a dome, and the second wall 104 may have a planar shape, such as a circle, oval, rectangle, or square, with a generally cylindrical side wall 106 therebetween.

The side wall(s) 106 of the housing 101 may be flexible to allow the housing 101 to expand when inflated and collapse when deflated. Exemplary materials suitable for the side wall(s) 106 include plastics, e.g., polyvinylchloride (PVC), polyethylene (PE), thermoplastic polyurethane (TPU), and other polymers, in a flexible form, such as a sheet. In some embodiments, the housing 101 may be transparent, e.g., comprising a clear plastic material such as PVC or TPU. In some embodiments, at least a portion of the material comprising the housing 101 may be biodegradable, e.g., a biodegradable polymer such as biodegradable TPU. The first and/or second walls 102, 104 may be relatively more rigid than the side wall(s) 106, e.g., comprising cardstock or a relatively rigid plastic

material, to provide the device **100** with sufficient stability to be free-standing when expanded. Any of the plastic materials used for the housing **101** may have a shiny or matte finish. In some embodiments, the housing **101** may be configured to produce a three-dimensional image, effect, or appearance.

The device **100** may be configured to emit light with a flashlight or spotlight effect. In some embodiments, the side wall(s) and/or second wall **104** may direct light emitted within the housing **101** towards the first wall **102** to exit the housing. For example, the side wall(s) **106** may include a translucent material providing for a frosted appearance or an opaque material that at least partially reflects light into the housing **101** to exit through the first wall **102**. The first wall **102** may comprise a transparent or at least partially transparent material, such as clear plastic, to allow the emitted light to pass therethrough.

The second wall **104** may include a solar panel **160**, and one or more of a power button **180**, a display **182**, and a sensor **184**. According to some embodiments of the present disclosure, each wall of the device that includes a solar panel may be referred to as an "electronics wall." Thus, the second wall **104** of device **100** may comprise an electronics wall, and may include one or more electronic components and/or electronic connections, e.g., as described below. The second wall **104** may be configured to allow the solar panel **160** to be exposed to natural and/or artificial light for charging/recharging the solar panel **160**.

The display **182** may be an LED display, and be configured to communicate information about the device **100**. For example, the display **182** may include a power level indicator to indicate the relative (e.g., percentage) and/or absolute amount of power or charge remaining in the device **100**. The dimensions of the display **182** may be suitable for displaying images and/or words. The sensor **184** may be configured to detect light, sound, motion, moisture, or any combination thereof. In at least one embodiment, the sensor **184** may be configured to detect environmental conditions such as lighting, sound, motion, and/or moisture conditions, and to adjust a parameter of the device **100** (e.g., power level, on/off, light intensity, and/or operating mode) based on the detected environmental conditions. Power button **180**, display **182**, and/or sensor **184** may be positioned anywhere on the second wall **104** other than as depicted in FIG. 1B, or anywhere on the first wall **102** or the side wall(s) **106**.

The device **100** may include a valve **110**, e.g., extending through the first wall **102**, to allow for the passage of air to inflate and deflate the device **100**. Closing the valve **110** may seal the housing **101** such that the housing **101** is airtight and watertight. In some embodiments, the lowermost portion of the valve **110** may lie against the inner surface of the first wall **102**, with the upper portion of the valve **110** extending above the outer surface of the first wall **102** to allow the user to inflate and deflate the housing **101**. The valve **110** may be flexible, e.g., comprising PVC or other suitable plastics or polymers. In some embodiments, for example, the upper portion of the valve **110** may be movable through an opening in the first wall **102** (or other portion of the housing **101**, such as a side wall **106** or the second wall **104**) by pressing on the valve **110**. Thus, a user may invert at least a portion of the valve **110** to provide for a planar outer surface of the housing **101**. The valve **110** may be configured for manual and/or automated inflation. In some embodiments, the valve **110** may be a pinch valve. The size dimensions of the valve **110** and/or its location on the housing **101** may vary according to the size, shape, and configuration of the housing **101**.

FIG. 1C shows an exploded view of the device **100**, showing components of the first wall **102** and the second wall **104**.

For example, the second wall **104** may include an inner panel **120** (e.g., a second inner panel **120** for devices that include a first inner panel **130**, discussed below), a reflector **122**, a printed circuit board (PCB) assembly **124**, a frame **126**, and an outer panel **128** (e.g., a second outer panel **128** for devices that include a first outer panel **138**, discussed below). The PCB assembly **124** may include at least one battery **150**, which may be operably connected to the solar panel **160**. For example, the battery **150** may be configured to store energy generated by the solar panel **160**. In some embodiments, the solar panel **160** may be coupled to the surface of the PCB assembly **124** opposite the surface that includes the battery **150**. Exemplary batteries **150** suitable for the device **100** include, but are not limited to, lithium-ion batteries such as a lithium-ion polymer, and lithium iron phosphate batteries. The battery **150** may generate a voltage from about 2V to about 5V, such as from about 3V to about 4V, e.g., a voltage of about 3.2V, about 3.5V, or about 3.7V. The battery **150** may have a capacity up to at least 2000 mAh, such as a capacity of about 500 mAh, about 750 mAh, about 1000 mAh, about 1250 mAh, about 1500 mAh, about 1750 mAh, or about 2000 mAh. For example, the capacity of the battery may be sufficient to charge an electronic device such as a mobile phone, for example a smart phone (see discussion of devices **600**, **700**, **800**, **900**, **1000**, and **1100** below).

In some embodiments, the device **100** may include a power supply, e.g., for use in addition to, or as an alternative to, solar power. For example, the device **100** may include a separate DC power supply. In some embodiments, the device **100** may include a first battery **150** configured to store energy generated by the solar panel **160**, and a second battery **150** configured to power the display **182**, e.g., to monitor the power level of the first battery **150**. The device **100** may include surge protection, e.g., to protect against voltage spikes, and/or may include a current regulator, e.g., to maintain a desired output of light. For example, a surge protector and/or current regulator may be coupled to the PCB assembly **124** and in communication with the battery **150**. In some embodiments, the device **100** may include a field-effect transistor (FET) to maintain a substantially constant current over time, e.g., as the battery **150** drains of power, to maintain consistent light output from the device **100**.

The device **100** may include at least one light **155**, such as a light-emitting diode (LED). While FIGS. 1A and 1C show device **100** as including 10 lights **155**, any number of lights **155** may be used. For example, the device **100** may include one light **155** (see, e.g., FIGS. 12A and 12B discussed below), or a plurality of 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, or 20 or more lights **155**. In some embodiments, for example, the number of lights **155** of the device **100** may range from about 10 to about 50, such as from about 20 to about 40, or from about 25 to about 35. The lights **155** may be different colors, and may be configured to emit visible light (e.g., red, orange, yellow, green, blue, violet, and/or white light), infrared light, and/or ultraviolet light (e.g., UV-A, UV-B, and/or UV-C). In some embodiments, the lights **155** configured to emit different wavelengths of light, e.g., combinations of visible light LEDs and UV light LEDs, or visible light LEDs and infrared LEDs. The lights **155** may be configured to alternate or cycle between different wavelength of light, such as alternating red, orange, yellow, green, blue, violet, and white light, and may be combined to generate additional hues of light, such as magenta, cyan, and amber.

The light(s) **155** may be coupled to the PCB assembly **124**. The lights **155** may have any suitable arrangement on the PCB, e.g., disposed around the battery **150**, on opposite sides of the battery **150**, adjacent to the battery **150**, etc. The lights

**155** may be positioned or oriented to emit light generally perpendicular to the PCB assembly **124**, or may be positioned or oriented at an incline in order to emit light at a non-perpendicular angle.

The PCB assembly **124** may include a microprocessor **153** configured to control the device **100** in different operating modes and/or a transceiver **157** for transmitting and/or receiving data wirelessly. For example, the microprocessor **153** may be configured to turn the device **100** on or off, dim one or more light(s) **155**, and/or turn various lights **155** on or off to achieve a particular color or effect. In some embodiments, the transceiver **157** may receive data from a remote control **170**, from the Internet, and/or via Bluetooth technology, and transmit the data to the microprocessor **153** for initiating different operating modes of the device **100**. For example, a user may control the operating mode of the device **100** via the remote control **170** and/or with a Bluetooth-enabled device. In some embodiments, multiple devices **100** may be configured to communicate with each other wirelessly, e.g., via Bluetooth technology. For example, a user may use a mobile app of a smart phone or other computing device to selectively control an operating mode of device **100**, or one or more devices **100**. In one embodiment, each device **100** may be provided with hardware and/or processing devices for implementing Z-wave, X-10, Insteon, Zigbee, C-Bus, EnOcean, KNX, and/or UPB home automation standards, for integrating one or more of devices **100** with a home automation or other smart-home system, and for control using a smartphone, television, touchscreen, voice control, or any other desired user interface. Thus, a user may selectively link together a plurality of devices **100** for integrated control, synchronized powering on, synchronized powering off, synchronized color changes, synchronized flickering, and so on. Moreover, the user may selectively link each device **100** with a smartphone and/or smart home system for controlling an operating mode of the device according to a location of the user, a location of the device relative to a geofence, a location of the device relative to another location, and/or a location of the device relative to another device.

As mentioned above, the solar panel **160** may be disposed opposite the PCB assembly **124**. Any suitable solar panel **160** may be used in the device **100**. In some embodiments, the solar panel **160** may comprise silicon, e.g., polycrystalline silicon, backed by a support material, such as polycarbonate or other plastic or polymer. Exemplary voltages of the solar panel **160** may generally range from about 4V to about 8V, e.g., about 5V, about 6V, or about 7V, but other voltages are encompassed by the disclosure herein.

The power button **180**, display **182**, and sensor **184** may be coupled to the PCB assembly **124** on the same side as the solar panel **160**, as shown in FIG. 1B. The solar panel **160** may comprise two arrays of solar cells with space therebetween, e.g., for placement of one or more of the power button **180**, display **182**, and sensor **184**. Thus, for example, the solar panel **160**, battery **150**, microprocessor **153**, lights **155**, power button **180**, display **182**, and sensor **184** may be in communication with one another via the PCB assembly **124** for operating and controlling the device **100**. The power button **180**, display **182**, and sensor **184** need not be between arrays of solar cells, however, and may be disposed on other portions of the PCB assembly **124**, e.g., adjacent to the solar panel **160**.

The frame **126** may be coupled to the PCB assembly **124**, and may include a window generally corresponding to the dimensions of the solar panel **160** to allow natural and/or artificial light to reach the solar panel **160** for charging. The frame **126** may include one or more other windows as needed to allow access to the power button **180**, display **182**, and/or

sensor **184**. Exemplary materials for the frame **126** include, but are not limited to, paper-based materials such as cardstock, and plastics and other polymers. The second outer panel **128** may comprise clear PVC or other materials that allow light to reach the solar panel **160** for charging. In some embodiments, the second outer panel **128** may overlay at least a portion of the power button **180**, display **182**, and/or sensor **184**, or may include cut-out areas to permit environmental exposure (e.g., allowing the sensor **184** to detect environmental conditions) and/or to permit uninhibited exposure to the solar panel **160**.

The reflector **122** may include one or more openings **123**, each opening **123** generally aligned with the one or more lights **155** of the PCB assembly **124**. For example, in the device **100** comprising ten lights **155** as shown in FIG. 1C, the reflector **122** may include ten openings **123**, one opening **123** generally aligned with each light **155** to allow emitted light to pass through the reflector **122** and into the housing **101**. The reflector **122** may be rigid, and may be configured to reflect emitted light from the inner surface of the reflector **122**. For example, the reflector **122** may comprise rigid PVC with reflective plating. The second inner panel **120** may comprise clear PVC or other materials that allow emitted light to pass into the housing **101**. The second inner panel **120** may form an airtight and/or watertight seal with the side wall(s) **106** to form an inflatable housing, and/or may form an airtight and/or watertight seal with the reflector **122**, e.g., to protect electronic components of the second wall **104** against humidity and/or possible damage.

Further referring to FIG. 1C, the first wall **102** may include an outer panel **138** (e.g., a first outer panel **138**), a disc **132**, and an inner panel **130** (e.g., a first inner panel **130**). In some embodiments, the disc **132** may be rigid, comprising a rigid plastic material such as Mylar (polyethylene terephthalate (PET)) or PVC. Similar to the reflector **122**, the disc **132** may be configured to reflect emitted light from the inside surface of the disc **132**. For example, the disc **132** may comprise a reflective coating or plating. The first inner panel **130** may comprise clear PVC or other materials that allow emitted light to pass therethrough to reach the disc **132** and reflect back into the housing **101**. The first inner panel **130** may form an airtight and/or watertight seal with the disc **132**. The first outer panel **138** may be flexible or rigid, e.g., comprising plastics such as PVC or other polymers, or paper-based materials such as cardstock. In some embodiments, at least a portion of each of the first inner panel **130**, disc **132**, and first outer panel **138** may comprise clear PVC or similarly transparent or translucent materials to allow light to pass through the first wall **102**. In some embodiments, at least a portion of the first wall **102** may be opaque.

FIG. 1C is exemplary, such that the device **100** may include additional or fewer components than shown. For example, in some embodiments, the device **100** may not include one or more of the second inner panel **120**, first inner panel **130**, or disc **132**.

At least a portion of the housing **101** may be transparent or translucent to allow the passage of light therethrough. For example, the first wall **102** and/or the side wall(s) **106**, or portions thereof, may be transparent, e.g., comprising a clear plastic material. In some embodiments, the first wall **102** and/or side wall(s) **106** may be at least partially translucent, e.g., such that light emitted inside the housing **101** may diffuse through the first wall **102** and/or side wall(s) **106**. Any of the first wall **102**, second wall, **104**, or side wall(s) **106** may be configured to affect the quality, hue, intensity, and/or amount of light that passes therethrough. In at least one embodiment, the side wall(s) **106** may be configured to dif-

fuse light to provide for a frosted effect or a warm, diffused glow. The inside surfaces of the housing **101** may be configured to enhance or diminish transmission of light through the housing **101**. For example, the inside surfaces one or more of the first wall **102**, second wall **104**, and side wall(s) **106** may include a reflective coating. Further, for example, portions of the housing **101** may be configured to selectively transmit or block particular wavelengths of light. Any of the first wall **102**, second wall **104**, or side wall(s) **106** may include different colors and/or patterns to affect the light that passes there-through.

As illustrated in FIG. 1D, the device **100** may include a design **195**, e.g., comprising graphics and/or lettering. The design **195** may be incorporated into the inside and/or outside surface(s) of the side wall(s) **106**, such as via etching, stenciling, an adhesive, or incorporated into the material of the side wall(s) **106**, or may comprise part of a screen or covering configured to fit on or around the device **100**. The design **195** may include different colors, textures, and/or or patterns configured to affect the diffusion of light therethrough. The design **195** may be seasonal (e.g., winter, summer, etc.), may relate to holidays (e.g., Halloween, Christmas, Hanukkah, Valentine's Day, etc.), may be associated with an event such as a birthday or anniversary, and/or may incorporate other types of designs, such as stellar constellations.

In some embodiments, the device **100** may include one or more handles **105**, e.g., for carrying the device **100**, or hanging the device **100** from a wall, ceiling, or other support. Referring to FIGS. 1A and 1B, for example, the device **100** may include a first handle **105a** on the outer surface of the first wall **102** (e.g., coupled to the first outer panel **138**), and a second handle **105b** on an outer surface of the second wall **104** (e.g., coupled to the second outer panel **128**). The second handle **105b** may be oriented with respect to the solar panel **160** to minimize overlap with the solar panel **160**. For example, the width of the second handle **105b** may generally overlay the space between arrays of solar cells on the solar panel **160**, as shown in FIG. 1B. Other orientations are possible, such as the second handle **105b** extending across solar cell arrays (see, e.g., FIG. 3B). In some embodiments, the device **100** may include only a first handle **105a**, only a second handle **105b**, or may not include any handles. The handles **105a**, **105b** may be flexible, e.g., such that they may lie flat against the housing **101** when not in use. Exemplary materials for the handles **105a**, **105b** include plastics such as PVC or PE, or other polymers.

The handles **105a**, **105b** may be fixedly attached to the housing **101** (e.g. via welding or permanent adhesive), or may be at least partially detachable. For example, one or both ends of each handle **105a**, **105b** may be detachable from the housing **101**, e.g., via a snap-fit connection, Velcro, or other suitable removable connection. In some embodiments, the handles **105a**, **105b** be integral with the housing **101**, forming part of the first wall **102** or the second wall **104**.

Other types of handles may be used for the devices disclosed herein. FIGS. 2A and 2B illustrate top and bottom views, respectively, of an exemplary device **200** that may include any of the features of device **100** described above. For example, the device **200** may include a housing **201**, and first and second handles **205a**, **205b** coupled to the housing **201**. One or both handles **205a**, **205b** may include a loop **207a**, **207b**, e.g., to facilitate hanging the device **200** from a support.

In some embodiments, the device **200** may include an adapter assembly **215** corresponding to each handle **205a**, **205b**, e.g., for clipping the device **200** to a support. For example, the adapter assembly **215** may facilitate transporting the device **200**, e.g., by clipping the device **200** to a

backpack or bicycle. The adapter assembly **215** may be configured to attach to the loop **207a**, **207b** via any suitable removable connection, such as a split ring or carabiner. In at least one embodiment, the adapter assembly **215** may comprise a split ring coupled to a barrel swivel (fishing swivel). The loops **207a**, **207b** of the handles **205a**, **205b** may be relatively rigid or reinforced to increase their durability for repeated clipping and unclipping.

FIGS. 3A-3C illustrate another exemplary device **300**, which may be collapsible and portable, and may include any of the features of devices **100** and/or **200** discussed above. In some embodiments, the device **300** may include a housing **301** with dimensions that make it relatively more compact than device **100** discussed above, e.g., having a smaller height and/or width. In some embodiments, the dimensions and/or operating modes of the device **300** may be useful in case of emergency (see discussion below), although the device **300** is not limited to such uses. The housing **301** may include a first wall **302**, a second wall **304**, and one or more side walls **306**, e.g., one generally cylindrical side wall **306**. The first wall **302** may include a valve **310**, e.g., substantially similar to the valve **110** of device **100**. The second wall **104** may include a solar panel **360** and power button **380**, e.g., substantially similar to the solar panel **160** and power button **180**, respectively, discussed above. While not shown, the device **300** may include a display, e.g., a power level indicator, and/or may include a sensor substantially similar to the display **182** and sensor **184**, respectively, discussed above.

As shown in the exploded view of FIG. 3C, the first wall **302** may include a first outer panel **338**, a disc **332**, and a first inner panel **330**; and the second wall **304** may include a second inner panel **320**, a reflector **322**, a PCB assembly **324**, a frame **326**, and a second outer panel **328**. The PCB assembly **324** may include any of the features of the PCB assembly **124** discussed above. For example, the PCB assembly **324** may include a battery **350**, such as a lithium iron phosphate battery, and one or more lights **355**, e.g., a plurality of LEDs (e.g., four LEDs as shown). The lights **355** may be disposed in a pattern in the central area of the PCB assembly **324**, as illustrated in FIG. 3C, or any other suitable arrangement. The reflector **322** may include an opening **323** generally aligned with each light **355**, e.g., a plurality of four openings **323** to allow emitted light to pass through the reflector **322** and into the housing **301**. The reflector **322** may comprise a rigid plastic such as PVC with a reflective plating or coating. The second inner panel **320** may be flexible, and may comprise clear PVC or other materials configured to allow light emitted from the LEDs to pass into the housing **301**. While not shown, the PCB assembly **324** may include a microprocessor substantially similar to the microprocessor **153** discussed above, e.g., for operating and controlling the device **300**.

In some embodiments, the inner surface of the second wall **304** may be at least partially inclined. For example, the reflector **322** and/or the second inner panel **320** may have inclined edges to form a generally frustoconical shape. The second inner panel **320** may form an airtight and/or watertight seal with the reflector **322**.

As mentioned above, devices according to the present disclosure may be configured to provide for a flashlight or spotlight effect. FIGS. 12A and 12B show an exemplary device **1200**, which may include any of the features of devices **100**, **200**, and/or **300** discussed above. For example, the device **1200** may include a housing including a first wall **1202**, a second wall **1204**, and one or more side walls **1206**. The first wall **1202** may include a valve **1210**, e.g., substantially similar to valves **110** and/or **310** of devices **100** and **300**, respectively. The second wall **1204** may include a solar panel **1260**,

which may be substantially similar to solar panels **160** and/or **360** of devices **100** and **300**, respectively, a handle **1205**, and a power button **1280**.

As shown, the device **1200** may include only one light, e.g., one LED **1255**, coupled to a portion of the second wall **1204**, such as a PCB assembly. The LED **1255** may be configured to emit any color of light and/or to cycle between different colors. The second wall **1204** may include a reflector **1222**, which may include any of the features of reflectors **122** and/or **322** of devices **100** or **300**, respectively. The reflector **1222** may include a single opening **1223** generally aligned with the LED **1255** to allow light emitted from the LED **1255** to pass through the reflector **1222** and into the housing. In some embodiments, the inner surface **1222a** of the reflector **1222** may be reflective, and may be concave in order to focus the light towards the center of the first wall **1202** to exit the housing. For example, at least a portion of the first wall **1202** may be transparent or translucent to allow light to pass through. In some embodiments, the side wall(s) **1206** may be configured to at least partially reflect light emitted from the LED **1255** into the housing to exit through the first wall **1202**, or may be configured to at least partially block light from exiting through the side wall(s) **1206** in order to exit through the first wall **1202**.

The present disclosure is not limited to the particular configurations and features depicted in the figures and discussed above. For example, devices according to the present disclosure may include other types and configurations of valves than valves **110**, **210**, **310** and **1210** discussed above, e.g., configured to control the ingress and egress of air (or other suitable gas) into and out of the devices.

Any of the devices disclosed herein may be configured to operate according to at least one protocol or operating mode. While the following discussion may refer to certain features of the device **100** of FIGS. **1A-1D** for illustration purposes, the features and principles are applicable to any other device disclosed herein.

In an exemplary “normal” operating mode, the device **100** may operate within a set of default or average operating parameters. For example, initiating the normal mode may cause the battery **150** to operate at an average voltage, and may turn on all or only some of the lights **155** (e.g., LEDs). In a “sleep” or “off” operating mode, all lights **155** (e.g., LEDs), of the device **100** may be turned off. In some embodiments, the battery **150** may continue to provide power to one or more other components of the PCB assembly **124**, such as the sensor **184**, microprocessor **153**, and/or transceiver **157**.

The device **100** may include one or more operating modes wherein the battery **150** may operate at voltages greater or less than the average voltage, e.g., causing the LEDs to brighten or dim, respectively. In some embodiments, the battery **150** may operate with pulse width modulation (PWM), wherein the battery voltage may be modified (increased or decreased) by changing the duty cycle. For example, the duty cycle may be changed to cause the LEDs to flash on and off in a “flash” or “emergency” mode. All or some of the LEDs may flash on and off regularly and/or in a specific pattern. For example, the LEDs may flash on and off to communicate textual information, such as the “SOS” distress signal in Morse code. Further, flashing frequency may operate as a timer, wherein each flash of light emitted by the device **100** corresponds to a predetermined unit of time. For example, the device **100** include an operating mode wherein one or more LEDs may flash in a regular pattern, such as one flash per second, per 2 seconds, per 5 seconds, etc. In some embodiments, the device **100** may include a “flicker” operating mode to simulate flickering candle light, e.g., according to an algo-

rithm of the microprocessor **153**. Further, the device **100** may include different operating modes with more frequent flickering, e.g., in a “windy” operating mode, and less frequent flickering, e.g., in a “calm” operating mode.

In some embodiments, the device **100** may include LEDs or other lights **155** configured to emit different types and/or colors of light (e.g., multicolor LEDs) or light-specific (e.g., red LEDs, blue LEDs, etc.), such that the operating modes may selectively control each LED to achieve a particular color or effect. The device **100** may have a different operating mode for each color, e.g., “red,” “orange,” “yellow,” “green,” “blue,” “violet,” and “white” modes, and/or color combinations thereof, such as “magenta,” “cyan,” and “amber” modes. In some embodiments, the device **100** may be used as a fishing light attractor, e.g., wherein operating the device **100** in a “green” operating mode may attract fish towards the light.

Further, the device **100** may have one or more different operating modes for each type of light, such as “infrared” and/or “UV” modes. In some embodiments, for example, the device **100** may include a “UV” operating mode configured for water disinfection/sterilization, e.g., emitting shortwave or UV-C light within a suitable wavelength range, such as from about 250 nm to about 270 nm. In some embodiments, the device **100** may have a “UV” operating mode emitting longer wavelengths of UV light, e.g., UV-A, for recreational use, such as from about 315 nm to about 400 nm. In some embodiments, the device **100** may include an “infrared” operating mode as a heat source, e.g., a low-grade or temporary source of heat.

In some embodiments, the device **100** may have at least “blue” and “red” operating modes, e.g., for use in a diurnal setting. For example, a user may select the “blue” mode during the day, e.g., for an energy boost, and the “red” mode at night, e.g., to facilitate sleep or as a night light. The device **100** may include additional operating modes responsive to environmental conditions detected by the sensor **184**. For example, the sensor **184** may be configured to detect environmental light to determine the diurnal cycle automatically. Thus, for example, the device **100** may have a “diurnal” operating mode that automatically cycles the device **100** between “red” and “blue” operating modes according to the diurnal cycle detected by the sensor **184**.

Further, the device **100** may have operating modes for turning the device **100** on and off based on information from the sensor **184**. In some embodiments, the sensor **184** may be configured to detect environmental lighting conditions, such that the device **100** may have an “auto on/off” operating mode wherein the device **100** may turn on or off based on an amount of light detected by the sensor **184**. For example, the device **100** may turn all LEDs on when the sensor **184** detects light equal or greater than a threshold value, and/or may turn all LEDs off when the light falls below the threshold value, or vice versa.

In some embodiments, the device **100** may be configured to generate sound. For example, the device **100** may include a speaker integrated into the device **100** and/or an audio output for connection to an external speaker or audio-generating or audio-amplifying device. The device **100** may include one or more operating modes for generating various sounds, including, but not limited to, white noise, babbling brook, wind, lightning storm, bird sounds, crickets, waterfall, rainfall, and/or crashing waves, among other natural soundscapes. Further, the device **100** may play music, e.g., via an integrated MP3 player (or other suitable audio player) and/or by connecting the device **100** to an MP3 player (or other suitable audio player).

13

Various operating modes of the device **100** may combine light and sound. For example, the device **100** may be configured to modify light output from one or more lights **155** according to the sound and/or rhythm of music generated and/or detected by the device **100**. For example, the sensor **184** may be configured to detect one or more characteristics of the sound waves, e.g., frequency (pitch), amplitude (loudness), and/or rhythmic patterns. Data from the sensor **184** may be communicated to the microprocessor **153** for operating and controlling the device **100** based on the one or more characteristics of the sound waves. In one embodiment, the color and/or intensity of light may be automatically adjusted based on a detected tone of music and/or a tone of a detected human voice. Alternatively, the color and/or intensity of light may change based on a detected volume of sound (music or voice), a detected pitch of sound (music or voice), or a detected mood of sound (music or voice).

In some embodiments, the device **100** may be configured to cycle through two or more different operating modes. Each operating mode may be initiated on-demand via user input and/or may operate according to an automatic transition sequence. In some embodiments, for example, each push of the power button (e.g., power button **180** of device **100** shown in FIG. 1B) may initiate a change of the LED color from one color to the next, between being in an off position to being in an “on” position. For example, a first push of the button may select a first color, a second push of the button may select a second color, and so on. Alternatively or additionally, the power button may be selectively operated to place the device in an automatic “color cycling” mode, e.g., a transition sequence. For example, the device **100** may include a “color cycle” operating mode that changes colors according to a preset or randomized algorithm of the microprocessor **153**. For example, in a “color cycle” operating mode, the device **100** may alternate or cycle between multiple colors, e.g., from red light to green, blue, magenta, yellow, cyan, orange, and white light, reinitiating the cycle by emitting red light, etc. The “color cycle” operating mode may include any number of colors and/or sequence of colors. The device **100** may emit each color of light for a given period of time before changing to the next color. For example, the device **100** may emit red light (or any other color) from about 3 second to about 5 minutes, e.g., about 5, about 10, about 15, about 30, or about 45 seconds, about 1 minute, or about 3 minutes. The device **100** may fade in and out of each color, such that one color gradually transitions into the subsequent color, e.g., over a period of time from about 1 second to about 5 seconds, e.g., about 2 or 3 seconds. The device **100** may achieve a fading effect by increasing and decreasing the intensity of the LEDs, e.g., via changing the PWM duty cycle with respect to each LED color. For example, the intensity of the LEDs may be changed to provide for fading in and out by modifying the duty cycle on the order of milliseconds.

In at least one embodiment, the microprocessor **153** is configured to control a plurality of operating modes of the LEDs based on selection of a button, e.g., the power button, for controlling selection of at least one of the operating modes of the LEDs. In one embodiment, the microprocessor **153** enables changing a color of light emitted from the housing such that a first press of the button causes the plurality of LEDs to emit a first color of light, a second press of the button causes the plurality of LEDs to emit a second color of light, a third press of the button causes the plurality of LEDs to emit a third color of light, and an nth press of the button causes the plurality of LEDs to initiate a transition sequence, the transition sequence causing the plurality of LEDs to begin emitting the first color of light, gradually change to the second color of

14

light, gradually change to the third color of light, and gradually change to the nth color of light. For example, a first press of the button may cause the LEDs to emit red light, a second press of the button may cause the LEDs to emit orange light, a third press of the button may cause the LEDs to emit yellow light, a fourth press of the button may cause the LEDs to emit green light, a fifth press of the button may cause the LEDs to emit green light, a sixth press of the button may cause the LEDs to emit blue light, and so on. In at least one embodiment, if the microprocessor is programmed to cause the button to selectively cycle between “n” colors, then pressing the button one more time, i.e., n+1 times, causes the microprocessor to initiate the LEDs to cycle through a transition sequence between all “n” colors.

For initiating different operating modes, the device **100** may accept input via the power button **180** (e.g., manual input), the sensor **184** (e.g., environmental input), and/or the transceiver **157** (e.g., wireless input). In some embodiments, pushing the power button **180** a certain number of times may signal the device **100** to initiate a particular operating mode. For example, pushing the power button **180** once may initiate a “normal” operating mode, turning all of the LEDs of the device **100** on (e.g., with respect to a “sleep” mode as discussed above), pushing the power button **180** twice may increase the intensity of the LEDs in a “high” operating mode, pushing the power button **180** three times may decrease the intensity of the LEDs in a “low” operating mode, pushing the power button **180** four times may cause the LEDs to flash in an “emergency” operating mode, and pushing the power button five times may turn all of the LEDs off, e.g., returning the device **100** to the “sleep” operating mode. In some embodiments, holding the power button **180** down for a specific amount of time may initiate different modes. For example, a user may push the power button **180** down for about 1 second to initiate the “normal” mode, about 2 seconds for the “high mode,” about 3 seconds for the “low” mode, about 4 seconds for the “emergency mode,” and about 5 seconds for the “sleep” mode.

In addition to manual input, or as an alternative, the device **100** may change between different operating modes based on data from the sensor **184**. As mentioned above, the sensor **184** may detect changes in one or more environmental conditions, such as lighting, sound, motion, and/or moisture. Once the parameter measured by the sensor **184** equals, exceeds, or falls below a threshold value, the microprocessor **153** may be programmed to initiate a particular operating cycle. Examples include the “diurnal,” and “auto on/off” operating modes discussed above, but are not limited to those examples, and are not limited to operating modes based on the sensor **184** measuring lighting conditions. Further, the device **100** may accept input wirelessly that signals to the device **100** to initiate different operating modes. For example, a user may use the remote control **170** to switch from one operating mode to another. In some embodiments, input via the power button **180** or wireless input via the transceiver **157** may override environmental input via the sensor **184**.

In some embodiments, the microprocessor **153** may be pre-programmed to initiate different modes at different times. For example, the microprocessor **153** may include an algorithm to run the device **100** in a “blue” operating mode from 7 am to 7 pm, and a “red” operating mode from 7 pm to 7 am. In some embodiments, input via the power button **180** or wireless input via the transceiver **157** may override the pre-programming of the microprocessor **153**. Any of the aforementioned operating modes may be combined with music,



e.g., an alarm operating mode wherein the device **100** plays music and/or adjusts light output at a predetermined time, such as a wake-up alarm.

While the above discussion illustrates exemplary inflatable devices **100**, **200**, **300**, and **1200**, the present disclosure is not limited to inflation. FIGS. **4A-4C** show an exemplary collapsible device **400** that need not be inflated to expand the device **400**. FIGS. **4A** and **4B** show top and bottom views, respectively, of the device **400** in a collapsed configuration, and FIG. **4C** shows the device **400** in an expanded configuration. The device **400** may comprise a housing **401** including a first wall **402**, a second wall **404**, and one or more side walls **406**. The side wall(s) **406** may include one or more folds **406a** in the width dimension (e.g., the fold(s) **406a** being substantially parallel to the first and second walls **402**, **404**) to allow the adjacent folded portions to collapse upon one another, e.g., similar to the bellows of an accordion.

The device **400** may include a spring-load mechanism, e.g., in the second wall **404**, which, when actuated, may cause the side wall(s) **406** to expand and/or collapse, thereby expanding and/or collapsing the housing **401**. For example, the spring-load mechanism may cause the first wall **402** to move away from the second wall **404** to expand the housing **401**, and/or to move towards the second wall **404** to collapse the housing **401**. In some embodiments, the device **400** may be inflatable, rather than spring-load expandable.

The side wall(s) **406** may include any of the shapes, sizes, configurations, and/or features of the side wall(s) **106** of device **100** discussed above. In some embodiments, the side wall(s) **406** may comprise polypropylene, e.g., with a shiny or matte finish. The side wall(s) **406** may comprise any other suitable materials, such as paper (e.g., paper with a plastic backing, or otherwise configured to be airtight and water tight or moisture-resistant) or other materials.

As shown in FIGS. **4A** and **4C**, the first wall **402** may be at least partially angled or inclined, having an angled surface **402a**. An inner portion **403** of the first wall **402** may be opaque, and may define an opening **409** configured to allow light to pass therethrough. For example, the opening **409** may comprise clear PVC or other transparent or translucent materials. In some embodiments, for example, the first wall **402** may include an outer sheet or covering of clear PVC. The angled surface **402a** or portions thereof may be opaque, transparent, or translucent. In some embodiments, the inner portion **403** may serve to focus light emitted from the housing **401** into a beam as it passes through the opening **409**. For example, the device **400** may provide a focused beam of light similar to a flashlight. In some embodiments, the inner portion **403** may comprise part of a removable sleeve or end cap configured to fit onto the first wall **402** to focus the light emitted from the housing **401**.

As shown in FIG. **4B**, the second wall **404** may include a solar panel **460**, which may include any of the features of the solar panel **106** of device **100** discussed above. In some embodiments, the solar panel **460** may include a single array of solar cells **406**, e.g., to maximize coverage of the second wall **406** for energy generation. The solar panel **460** may be coupled to a PCB assembly substantially similar to the PCB assembly **124** of the device **100** discussed above, e.g., the PCB assembly being coupled to a battery and one or more lights, such as LEDs. The solar panel **460** may be covered by clear PVC for protection and configured to allow exposure to natural and/or artificial light for charging the battery.

Each of the first wall **402** and the second wall **404** may comprise a rigid plastic material, a metal, a metal alloy, or a combination thereof. In some embodiments, each of the first and second walls **402**, **404** may comprise acrylonitrile buta-

diene styrene (ABS), e.g., injection-molded ABS, optionally with a metallized finish, e.g., metallized chrome finish. In some embodiments, the device **400** may include a handle **405** coupled to the housing. For example, the handle **405** may be attached to the second wall **404** as shown in FIG. **4B**. In some embodiments, the ends **405a** of the handle **405** may be configured to pivot with respect to the second wall **404** such that the handle **405** may lay flat against the second wall **404** when not in use.

The second wall **404** may include a power button **480**, and one or more of a timer button **481** and an electronic port **485**. The power button **480** may be used to control different operating modes of the device **400**, e.g., as described above with respect to the power button **180** of device **100**. The timer button **481** may be used to set a time at which an operating mode of the device **400** may be initiated. For example, the timer button **481** may correspond to initiation of a “dawn simulator” mode, wherein the lights (e.g., LEDs) of the device **400** gradually brighten to simulate sunrise. The “dawn simulator” mode may gradually turn on and/or increase the intensity of the LEDs over a period of time ranging from about 5 minutes to 1 hour, e.g., from about 15 minutes to about 45 minutes, e.g., about 30 minutes or about 45 minutes. In some embodiments, the device **400** may include a “diurnal” operating mode as discussed above, in combination with the “dawn simulator” mode. For example, initiation of the “dawn simulator” mode may include gradually transitioning from red light (e.g., primarily used at night) to blue light (e.g., primarily used during the day).

In some embodiments, the timer button **481** may program an integer number of hours until the “dawn simulator” mode commences. In some embodiments, holding the timer button **481** down may cause a timer LED to flash sequentially. The timer LED may be inside the housing **401**, located within the timer button **481** or the power button **480**, or may be a separate LED indicator on the housing **401**. Holding the timer button **481** for about 1 second may correspond to 1 flash of the timer LED and set 1 hour until the “dawn simulator” mode commences, holding for about 2 seconds may correspond to two flashes and 2 hours, etc. The timer button **481** may correspond to any other operating mode, including, but not limited to, any of the operating modes discussed above. Once the timer is set, the timer LED or one or more other lights/LEDs of the device **400** may flash a different color. In some embodiments, the timer button **481** may be used to initiate the “sleep” mode of the device **400**, thereby canceling or overriding any other operating mode. The timer button **481** therefore may allow a user to turn the LEDs off without the need to cycle through other operating modes. In at least one embodiment, the device **400** may receive timing information for initiating different operating modes wirelessly or remotely. For example, the device **400** may receive input associated with the location, time zone, etc., of the device **400** from an application (“app”) on a mobile phone, a GPS device, or airplane navigation system, e.g., for syncing the device **400** to the appropriate time zone or diurnal cycle when changing locations, such as during travel. Any other devices disclosed herein may include a timer button **481**, e.g., for setting a desired time for a particular operating mode to begin.

FIG. **5** illustrates exemplary packaging **590** for a device **500**, suitable for a point-of-purchase display. The device **500** may include any of the features of devices **100**, **200**, **300**, **1200**, and/or **400** discussed above. For example, the device may include a solar panel **560**, which may be visible through a clear window of the packaging **590**. The window may comprise a clear plastic that allows natural and/or artificial light to pass through the packaging **590** to reach the solar panel **560**.

Thus, the device 500 may charge while on display, such that it may be ready for use upon removal from the packaging 590. The packaging 590 may comprise any material or combination of materials to protect the device 500 while on display. Exemplary materials include, but are not limited to, rigid materials such as cardboard or plastic.

Devices according to the present disclosure may be configured to use solar energy generated and stored in the devices to provide power to other electronics, e.g., as a charger. For example, the devices disclosed herein may include at least one electronic connector compatible with one or more electronic devices. Exemplary electronic connectors include, but are not limited to USB and USB-like connectors (USB-A, USB-B, micro-USB, etc.) and Lightning connectors (e.g., for electronic devices manufactured by Apple). Any of the electronic connectors disclosed herein may be male or female connections.

FIGS. 6A and 6B illustrate alternative configurations of an exemplary device 600, which may include any of the features of devices 100, 200, 300, 1200, 400, and/or 500 discussed above. The device 600 may comprise a housing that includes a second wall 604 and one or more side walls 606, e.g., a single cylindrical side wall 606 as shown, or any other number of side walls 606. The second wall 604 may include a solar panel 660.

In the configuration shown in FIG. 6A, the perimeter of the second wall 604 (or the portion of the side wall(s) 606 adjacent to the second wall 604) may include a recessed area or groove 640a, and a cord 644a configured to fit within the groove 640a. In some embodiments, the cord 644a may have a generally circular cross-section. The end of the cord 644a may include an electronic connector 645a, such as an electronic adapter or port compatible with one or more electronic devices. The cord 644a may be fixedly attached to an end 641a of the groove 640a. The cord 644a may be flexible, such that the end of the cord 644a including the electronic connector 645a may be detached and pulled away from the groove 640a in use, e.g., to charge an electronic device, such as a mobile phone, tablet device, mp3 player, and/or other portable electronic devices. The cord 644a may be operably coupled to the solar panel 660 and battery inside the device 600 in order to supply power to the electronic device. For example, the end of the cord 644a opposite the electronic connector 645a may connect to the battery of the device 600 inside the second wall 604. While not in use, the electronic connector 645a may fit securely within a cavity 647a along the groove 640a.

The configuration shown in FIG. 6B is similar to that of FIG. 6A, comprising a recessed area or groove 640b extending along the perimeter of the second wall 604, and a cord 644b configured to fit within the groove 640b. The cord 644b may have a generally rectangular cross-section, e.g., with a relatively narrow depth providing for a flat shape. The cord 644b may be flexible, and may include an electronic connector 645b compatible with one or more electronic devices. The cord 644b may be fixedly attached to an end 641b of the groove 640b. Similar to cord 644a, the cord 644b of FIG. 6B may be operably coupled to the solar panel 660 and the battery to provide power to the one or more electronic devices. While not in use, the electronic connector 645b may fit securely within a cavity 647b along the groove 640b.

FIGS. 7A and 7B illustrate different configurations of an exemplary device 700, which may include any of the features of devices 100, 200, 300, 1200, 400, 500, and/or 600 discussed above. The device 700 may comprise a housing that includes a first wall 702, a second wall 704, and one or more side walls 706. The second wall 704 may include a solar panel

760, and the first wall 702 may include a valve 710, e.g., for inflating the housing. In some embodiments, the device 700 may not include a valve 710, and may be configured for expansion via a spring-load mechanism or other suitable expansion mechanism.

In the configuration shown in FIG. 7A, the device 700 may include a flexible cord 744a configured to lay against the side of the second wall 704, e.g., adjacent to the side wall(s) 706. The cord 744a may include an electronic connector 745a, and may be operably coupled to the solar panel 760 and a battery inside the device 700. While not in use, the electronic connector 745a may fit securely within a cavity 747a of the second wall 704, e.g., in a stored position. The cord 744a may include a flexible tab 746a configured to be gripped by a user, e.g., to facilitate removing the electronic connector 745a from the cavity 747a by pulling on the tab 746a.

In the configuration shown in FIG. 7B, the device 700 may include a flexible cord 744b configured to lay against the first wall 702, e.g., in a stored position. The cord 744b may include an electronic connector 745b, and may be operably coupled to the solar panel 760 and battery inside the device 700 via a section 748 of the cord 744b extending from the first wall 702 to the second wall 704. While not in use, the electronic connector 745a may fit securely within a cavity 747b of the first wall 704. The cord 744b may include a flexible tab 746b, similar to the tab 746a of FIG. 7A.

The configurations shown in FIGS. 7A and 7B may be alternatives of each other, e.g., the device 700 comprising either cord 744a or cord 744b. In some embodiments, however, the device 700 may comprise both cord 744a (attached to the second wall 704) and cord 744b (attached to the first wall 702 and operably coupled to the solar panel 760 of the second wall 704), wherein the electronic connectors 745a, 745b may be the same or different types of connectors.

FIG. 8 illustrates yet another exemplary device 800 including an electronic connector 845 compatible with one or more other electronic devices. The device 800 may include any of the features of devices 100, 200, 300, 1200, 400, 500, 600, and/or 700 discussed above. As shown, the device 800 may include a first wall 802, and a cord 844 extending through an opening in the first wall 802. One end of the cord 844 may include an electronic connector 845, and the other end of the cord may be operably coupled to a solar panel and battery of the device 800, e.g., in the second wall 804 of the device 800. For example, a section 848 of the cord 844 may extend between the first wall 802 and the second wall 804. In some embodiments, a portion of the cord 844 may be embedded within the first wall 802 (e.g., between a disc and a first outer panel similar to the disc 132 and the first outer panel 138, respectively, of device 100). In some embodiments, the first wall 802 may include a lumen configured to receive a portion of the cord 844. The outer surface of the first wall 802 may include a groove 840 to receive the cord 844 when not in use, e.g., in a stored position. For example, the electronic connector 845 may fit securely within a cavity 847 at the end of the groove 840.

While FIG. 8 illustrates the cord 844 extending from the first wall 802, in some embodiments, the cord 844 may extend from an opening in the side wall(s) 806 or the second wall 804. For example, the second wall 804 may include the solar panel, and a groove 840 adjacent to the solar panel, e.g., extending in an arc around a portion of the solar panel.

FIGS. 9A and 9B illustrate alternative configurations of an exemplary device 900, which may include any of the features of devices 100, 200, 300, 1200, 400, 500, 600, 700, and/or 800 discussed above. The device 900 may comprise a housing

that includes a second wall **904** and one or more side walls **906**. The second wall **904** may include a solar panel **960**.

The configuration of the device **900** shown in FIG. **9A** may be similar to the configuration of the device **600** shown in FIG. **6A**. For example, the device **900** may comprise a second wall **904** and one or more side walls **906**, wherein the second wall **904** includes a recessed area or groove **940**, and a cord **944a** configured to fit within the groove **940**. The end of the cord **944a** may include an electronic connector **945a** compatible with one or more electronic devices. The cord **944a** may be operably coupled to a solar panel **960** and battery of the device **900**. Rather than being fixedly attached to a portion of the groove **940**, however, the cord **944a** may be retractable, such that a user may pull the cord **944a** to withdraw a longer length of the cord **944a** from the device **900**. The retraction mechanism also may allow the user to adjust the length of the cord **944a** by reinserting a portion of the cord **944a** into an internal portion of the groove **940**. The retraction mechanism therefore may allow the user to adjust slack in the cord **944a** to facilitate inserting the electronic connector **945** into an electronic device, e.g., for charging. An end of the groove **940** may include a cavity **947a** to receive the electronic connector **945**, e.g., in a stored position.

The configuration shown in FIG. **9B** shows an alternative configuration of the device **900**, comprising an opening **947b** in the side of the second wall **904** through which a cord **944b** may extend. The device **900** may include a retraction mechanism coupled to the second wall **904** to allow a user to increase slack in the cord **944b** by pulling on the cord **944b** in the direction of the arrow. The retraction mechanism also may allow the user to decrease slack in the cord **944a** by reinserting a portion of the cord **944b** into an internal cavity or groove. A portion of the cord **942** proximate the electronic connector **945** may have a greater cross-sectional area than the opening **947b** to stop the cord **944b** from completely withdrawing into the device **900**.

FIGS. **10A** and **10B** illustrate an exemplary device **1000** also comprising a retraction mechanism. The device **1000** may include any of the features of devices **100**, **200**, **300**, **1200**, **400**, **500**, **600**, **700**, **800**, and/or **900** discussed above. As shown, the device **1000** may comprise a housing including a first wall **1002**, which may include a valve **1010**, and one or more side walls **1006**. The device **1000** may include a cord **1044** comprising an electronic connector **1045**, wherein the cord **1044** extends from an opening **1047** in the first wall **1002**. The retraction mechanism may operate similarly to those discussed above in connection to device **900**, e.g., to allow a user to adjust slack in the cord **1044**. The cord **1044** may include features to prevent the cord **1044** from completely withdrawing into the device **1000**. For example, a proximal portion of the cord **1044** may have a cross-sectional area greater than a cross-sectional area of the opening **1047**.

The first wall **1002** may include a latching mechanism, such as a stopper **1041**, to cover the cord **1044** and the opening **1047** when the cord **1044** is not in use, e.g., in a stored position. The stopper **1041** may have a shape compatible with a recessed area **1042** around the opening **1047**, e.g., to form a seal when closed as shown in FIG. **10B**. The stopper **1041** may include a tab **1046** configured to be gripped by a user to facilitate opening the stopper **1041** to access the cord **1044**. The end of the cord **1045** opposite the electronic connector **1045** may be operably coupled to a solar panel and battery of the device **1000**, e.g., in the second wall **1004** of the device **1000**. For example, a section **1048** of the cord **1044** may extend between the first wall **1002** and the second wall **1004**. In some embodiments, a portion of the cord **1044** may extend between portions of the first wall **1002**, similar to device **800**

discussed above, such that the cord **1044** may be isolated from the interior of the housing. Thus, a user may withdraw and reinsert the cord **1044** when the housing is expanded and during use of the device **1000**, e.g., without compromising an airtight and watertight seal of the expanded housing.

While FIGS. **10A** and **10B** illustrate the cord **1044** extending from the first wall **1002**, in some embodiments, the cord **1044** may extend from an opening in the side wall(s) **1006** or the second wall **1004**. For example, the second wall **1004** may include the stopper **1041**, e.g., adjacent to the solar panel.

In addition to, or as an alternative to the electronic connectors discussed above, devices according to the present disclosure may be configured to charge electronic devices via an induction pad. FIG. **11** illustrates an exemplary device **1100**, which may include any of the features of devices **100**, **200**, **300**, **1200**, **400**, **500**, **600**, **700**, **800**, **900**, and/or **1000** discussed above. As shown, the device **1100** may comprise a housing including a second wall **1104**, a first wall, and one or more side walls **1106** therebetween. The side wall(s) **1106** may be flexible to allow the housing to collapse (as shown in FIG. **11**) and expand. The second wall **1104** may include a solar panel **1160**, and the first wall **1102** may include an induction pad **1190** operably coupled to the solar panel **1160** and to a battery of the device **1100** (not shown) likewise coupled to the solar panel **1160**.

For example, the induction pad **1190** may be positioned sufficiently close to the solar panel **1160** and battery for charging, e.g., when the device **1100** is in a collapsed configuration such that the first and second walls **1102**, **1104** are in close proximity. In some embodiments, the induction pad **1190** may be directly coupled to the solar panel **1160** and battery, e.g., the induction pad **1190** being directly coupled to the second wall **1104**. Further, in some embodiments, the first wall **1102** and/or second wall **1104** may include a recessed area of suitable dimensions to receive the induction pad **1190** in a nested configuration. A user may place an electronic device **30**, such as a mobile phone, against the induction pad **1190** to charge the electronic device **30**. By placing the device **1100** such that the solar panel **1160** is exposed to natural or artificial light, and the induction pad **1190** below is in contact with the electronic device **30**, the solar panel **1160** may simultaneously generate and/or store energy while the induction pad **1190** charges the electronic device **30** via the generated/stored energy.

Any features disclosed herein in connection with one embodiment may be combined with any other embodiments. Other embodiments of the present disclosure will be apparent to those skilled in the art from consideration of the specification and practice of the embodiments disclosed herein. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the disclosure indicated by the following claims.

We claim:

1. A collapsible solar-powered lighting device comprising: a housing including a first wall, a second wall opposite the first wall, and one or more side walls extending between the first wall and the second wall, wherein the first wall, second wall, and one or more side walls define an inflatable bladder; at least one solar panel integrated into an outside surface of at least one of the first wall and the second wall, thereby defining the at least one of the first wall and the second wall that includes the at least one solar panel as an electronics wall of the housing; a plurality of light-emitting diodes (LEDs) integrated into an inside surface of the electronics wall of the housing,

## 21

the plurality of LEDs forming a generally annular arrangement and facing an interior of the housing;

a rechargeable battery integrated into the electronics wall between the inside surface of the electronics wall and the outside surface of the electronics wall, the rechargeable battery being electrically connected between the at least one solar panel and the plurality of LEDs, such that the rechargeable battery is configured to supply current to the plurality of LEDs and be recharged by the at least one solar panel;

a button integrated into one or more of the first wall, the second wall, and the one or more side walls, the button being selectable by a user to control an operating mode of the plurality of LEDs;

a microprocessor integrated into the electronics wall of the housing between the inside surface of the electronics wall and the outside surface of the electronics wall, the microprocessor being electrically connected to the button, the rechargeable battery, and the plurality of LEDs; and

a current regulator coupled between the rechargeable battery and the microprocessor, the current regulator maintaining a threshold current delivered to the plurality of LEDs as controlled by the microprocessor;

wherein the microprocessor is configured to control a plurality of operating modes of the LEDs, at least one of the operating modes including changing a color of light emitted from the housing such that a first press of the button causes the plurality of LEDs to emit a first color of light, a second press of the button causes the plurality of LEDs to emit a second color of light, a third press of the button causes the plurality of LEDs to emit a third color of light, and an nth press of the button causes the plurality of LEDs to initiate a transition sequence, the transition sequence causing the plurality of LEDs to begin emitting the first color of light, gradually change to the second color of light, gradually change to the third color of light, and gradually change to the nth color of light.

2. The device of claim 1, wherein the housing is inflatable to convert the housing from a collapsed configuration to an expanded configuration.

3. The device of claim 1, wherein at least a portion of the housing comprises a biodegradable material.

4. The device of claim 1, further comprising a sensor, wherein data collected by the sensor controls at least one operating mode of the device.

5. The device of claim 4, wherein the sensor is configured to detect light, sound, motion, moisture, or a combination thereof.

6. The device of claim 5, wherein the microprocessor is configured to initiate at least one operating mode of the device when the sensor detects an amount of environmental light above a threshold value.

7. The device of claim 6, wherein the at least one operating mode includes changing the color of light emitted from the housing between red light and blue light based on the amount of environmental light detected by the sensor.

8. The device of claim 1, wherein the plurality of operating modes includes adjusting an intensity of at least a portion of the LEDs to simulate flickering light.

9. The device of claim 1, further comprising at least one transceiver for receiving wireless input to control at least one operating mode of the device.

10. The device of claim 1, further comprising a cord coupled to the battery and extending outside of the housing, the cord including an electronic connector.

## 22

11. The device of claim 1, further comprising a display coupled to the battery for indicating an amount of power remaining in the battery.

12. The device of claim 1, wherein the plurality of LEDs includes LEDs that emit ultraviolet light.

13. The device of claim 1, further comprising at least one handle coupled to an outer surface of the housing and at least partially detachable from the housing.

14. An inflatable solar-powered lighting device comprising:

a housing including a first wall, a second wall opposite the first wall, and one or more side walls extending between the first wall and the second wall, wherein the first wall, second wall, and one or more side walls define an airtight inflatable bladder;

at least one solar panel integrated into an outside surface of at least one of the first wall and the second wall;

a plurality of light-emitting diodes (LEDs) integrated into an inside surface of the at least one of the first wall and the second wall, the plurality of LEDs arranged in a generally annular arrangement and facing an interior of the airtight inflatable bladder defined by the first wall, second wall, and one or more side walls;

a rechargeable battery integrated into the at least one of the first wall and the second wall between the inside surface of the at least one of the first wall and the second wall and the outside surface of the at least one of the first wall and the second wall, the rechargeable battery being electrically connected between the at least one solar panel and the plurality of LEDs, such that the rechargeable battery is configured to supply current to the plurality of LEDs and be recharged by the at least one solar panel;

a button integrated into one or more of the first wall, the second wall, and the one or more side walls, the button being selectable by a user to control an operating mode of the plurality of LEDs;

a microprocessor integrated into the at least one of the first wall and the second wall between the inside surface of the at least one of the first wall and the second wall and the outside surface of the at least one of the first wall and the second wall, the microprocessor being electrically connected between the button, the battery, and the plurality of LEDs; and

a current regulator coupled between the rechargeable battery and the microprocessor, the current regulator maintaining a threshold current delivered to the plurality of LEDs as controlled by the microprocessor;

wherein the microprocessor is configured to control a plurality of operating modes of the LEDs, at least one of the operating modes including changing a color of light emitted from the housing.

15. The device of claim 14, further comprising at least one transceiver configured to receive wireless input and transmit the wireless input to the microprocessor to control at least one operating mode of the device.

16. The device of claim 14, wherein the microprocessor includes an algorithm for controlling the LEDs to simulate flickering light.

17. The device of claim 14, wherein the battery operates with pulse width modulation, and at least one operating mode of the device includes modifying a duty cycle of the battery to change an intensity of light emitted from the LEDs into the housing.

18. A collapsible solar-powered lighting device comprising:

a housing including a first wall, a second wall opposite the first wall, and one or more side walls extending between

23

the first wall and the second wall, wherein the first wall, second wall, and one or more side walls define an inflatable bladder;

at least one solar panel integrated into an outside surface of at least one of the first wall and the second wall, the solar panel defining the at least one of the first wall and the second wall as an electronics wall of the housing;

a plurality of light-emitting diodes (LEDs) integrated into an inside surface of the electronics wall of the housing, the plurality of LEDs arranged in a generally annular arrangement and facing an interior of the inflatable bladder defined by the first wall, second wall, and one or more side walls;

a rechargeable battery integrated into the electronics wall of the housing between the inside surface of the electronics wall and the outside surface of the electronics wall, the rechargeable battery being electrically connected between the at least one solar panel and the plurality of LEDs, such that the rechargeable battery is configured to supply current to the plurality of LEDs and be recharged by the at least one solar panel;

a button integrated into one or more of the first wall, the second wall, and the one or more side walls, the button being selectable by a user to control an operating mode of the plurality of LEDs; and

24

a microprocessor integrated into the electronics wall of the housing between the inside surface of the electronics wall and the outside surface of the electronics wall, the microprocessor being electrically connected between the button, the battery, and the plurality of LEDs;

wherein the microprocessor is configured to control a plurality of operating modes of the LEDs, at least one of the operating modes including changing a color of light emitted from the housing such that a first press of the button causes the plurality of LEDs to emit a first color of light, a second press of the button causes the plurality of LEDs to emit a second color of light, and a third press of the button causes the plurality of LEDs to emit a third color of light.

**19.** The device of claim **18**, wherein the sensor is configured to detect light, and the microprocessor is configured to initiate at least one operating mode of the device when the sensor detects an amount of light above a threshold value.

**20.** The device of claim **19**, wherein the microprocessor is configured to supply or terminate power to the plurality of LEDs when the amount of light detected by the sensor exceeds the threshold value.

\* \* \* \* \*